

**RESETABLE  
CALL POINT**



**GENERALSECURITY**



## GS-EXIT-O22W

- DPDT Resetable call point
- 2NO / 2NC / 2COM
- 3A/DC 36V(max momentary)
- White ABS material



VDC 12~24



Reusable Plastic Sheets

## FEATURES

- Supports continuous current of DC 12~24V, up to 2A
- Re-settable design, no need to replace glass after activation
- Plug-in terminal blocks for quick and easy wiring
- Includes protective cover and mounting box for added safety and convenience

**GENERALSECURITY.COM.AU**

## SPECIFICATION

### GS-EXIT-O22W

|                    |                                       |
|--------------------|---------------------------------------|
| Model              | GS-EXIT-022W                          |
| Size (mm)          | 97L*92W*59H                           |
| Weight (kg)        | 0.185                                 |
| Power Supply       | Max 2A@12~24VDC                       |
| Output Contact     | 2NO / 2NC / 2COM                      |
| Material           | ABS                                   |
| Color              | White                                 |
| Mechanical Life    | 500,000 tested (aging test qualified) |
| Installation       | Surface mount                         |
| Operating Temp     | -20°C~+70°C(-4-158F)                  |
| Operating Humidity | 0-95% (RH)                            |
| Package Quantity   | 1 PCS / Box, 100PCS / Carton          |

Front



Front



Side



Back

